

SuperMax Oil Germany Ready-To-Use ANTIFREEZE



PRODUCT DESCRIPTION

SuperMax Oil Germany READY-TO-USE ANTIFREEZE is a high qualified mono ethylene glycol based antifreeze that includes high performance additives for use in engine cooling systems. Thanks to its special formulation, it prevents freezing at cold climates and retards over heating at hot climates. It shows optimum performance in all kinds of vehicles with its ideal ready to use formulation

ADVANTAGES

- To prevent possible mistakes in dilution with water, it has been formulated as “ready to use”. It prevents corrosion and electrolyze formation.
- Provide high performance and long service life during usage period.
- Shows high performance at all kinds of climate conditions.
- It can be compatible with all kinds of sealing elements. It does not have any harmful effects on engine equipment.

CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Ideal Values
Color	-	-	Blue
Density 15,5 °C	g/cm3	ASTM D 4052	1.069
Reserve Alkalinity (pH=5,5)	mL	ASTM D 1121	7.1
Freeze Point (%100)	°C	ASTM D 1177	-37.5
Boiling Point (%100)	°C	ASTM D 482	110
pH, 20° C (%50 with water)	-	ASTM D 1287	10.12
pH, 20° C (%100)	-	ASTM D 1287	9.99

SuperMax Oil Germany Ready-To-Use ANTIFREEZE



ADDITIONAL INFORMATION

Package

- 1 L
- 3 L
- 16 kg
- 200 kg
- IBC
- Bulk

STORAGE

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use.

Packages should not be exposed to direct sunlight and avoid rapid climatic changes.

Ambient temperature should not exceed 60 °C.

SHELF LIFE

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

HEALTH AND SAFETY

Based on the available information, SuperMax Oil Germany Antifreeze ELC, is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations