

# SuperMax Oil Germany Agri Trans S422

## Transmission Oil for Agricultural Machines



### PRODUCT DESCRIPTION

SuperMax Oil Germany Agri Trans S422 is a transmission oil that has been formulated with high quality base oil. Prevents wear, foam and cuts out noise due to its EP and AW additives. It is developed for using in transmission and hydraulic system of tractors and final drive units of agricultural machines.

### ADVANTAGES

- It protects the power transmission system through EP and AW additives.
- Minimizes scabbing in the gear system.
- Prevents rust, corrosion and foam formation.
- Compatible with all seals.
- It provides very good cleaning of the gear system thanks to its thermal stability and resistance to oxidation.

### APPROVALS AND SPECIFICATIONS

- API GL-4
- Caterpillar TO-2
- Massey Ferguson CMS M1135

### CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Ideal Values
Density, @15° C	g/cm <sup>3</sup>	ASTM D 4052	0.889
Viscosity, @40° C	cSt	ASTM D 445	92.31
Viscosity, @100° C	cSt	ASTM D 445	10.54
Viscosity Index	-	ASTM D 2270	95
Pour Point	°C	ASTM D 97	-27
Flash Point	°C	ASTM D 92	220

# **SuperMax Oil Germany Agri Trans S422**

## **Transmission Oil for Agricultural Machines**



### **STORAGE**

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use. Packages should not be exposed to direct sunlight and avoid rapid climatic changes. Ambient temperature should not exceed 60 °C.

### **SHELF LIFE**

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

### **HEALTH AND SAFETY**

Based on the available information, SuperMax Oil Germany Agri Trans S422 are not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations