SuperMax Oil Germany 15W/40 (CF-4)

Long Life Protection for Turbo Diesel Engines

PRODUCT DESCRIPTION

SuperMax Oil Germany 15W/40 (CF-4) was formulated with special performance additives ensuring superior protection at high temperatures for diesel engines. SuperMax Oil Germany 15W/40 (CF-4) minimizes the oil utilization of turbo- and super-charged engines, prevents extreme oil consumption and ensures excellent protection for engines against wears.

ADVANTAGES

- Prevents deposit formation even at high temperatures.
- Prolongs the oil replacement period.
- It ensures oxidation, corrosion and foaming control.
- Ensures superior engine cleaning.

APPROVALS AND SPECIFICATIONS

• API CF-4

CHARACTERISTIC PROPERTIES

Viscosity Grade : SAE 15W / 40

Analysis	Unit	Analysis Method	Ideal Values
Density, 15°C	g/cm3	ASTM D 4052	0,8826
Viscosity, 40°C	cSt	ASTM D 445	107,8
Viscosity, 100°C	cSt	ASTM D 445	14,83
Viscosity Index	-	ASTM D 2270	139
Pour Point	°C	ASTM D 97	-27
Flash Point	°C	ASTM D 93	228

SuperMax

GERMANY

SuperMax Oil Germany 15W/40 (CF-4)



Long Life Protection for Turbo Diesel Engines

STORAGE

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be thightly closed and sealed when not in use. Packages should not be exposed to direct sunlight and avoid rapid climatic changes. Ambient temperature should not exceed 60 °C.

SHELF LIFE

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

HEALTH AND SAFETY

Based on the available information, SuperMax Oil Germany 15W/40 (CF-4) is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations