

SuperMax Oil Germany DOT 4

High Quality Hydraulic Brake System Fluid



PRODUCT DESCRIPTION

SuperMax Oil Germany DOT 4; is a synthetic based high quality hydraulic brake fluid, that has been developed to be used in hydraulic brake and clutch systems, which has high boiling point and provides optimum performance.

ADVANTAGES

- Due to its high viscosity index, it performs thrust duty perfectly even at high temperatures.
- High oxidation resistance provides long service life.
- Maximum corrosion protection in the brake systems due to its anti-corrosion additives.

APPROVALS AND SPECIFICATIONS

- FMVSS 116 DOT 4

CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Ideal Values
Density, 15°C	g/cm ³	ASTM D 4052	1,0719
Viscosity, 40°C	cSt	ASTM D 445	7,846
Viscosity, 100°C	cSt	ASTM D 445	2,150
Viscosity Index	-	ASTM D 2270	63
Pour Point	°C	ASTM D 1120	258
Flash Point	°C	ASTM D 93	130

STORAGE

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use. Packages should not be exposed to direct sunlight and avoid rapid climatic changes. Ambient temperature should not exceed 60 °C.

SuperMax Oil Germany DOT 4

High Quality Hydraulic Brake System Fluid



SHELF LIFE

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

HEALTH AND SAFETY

Based on the available information, SuperMax Oil Germany DOT 4 is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations