

SuperMax Oil Germany Steering Fluid



PRODUCT DESCRIPTION

Supermax Oil Germany Direksiyon Sıvısı is a steering fluid, formulated with well-refined paraffinic, mineral based oils and special additive package that provides oxidation stability, corrosion protection and defoaming capability.

ADVANTAGES

- Long service life due to high oxidation resistance.
- High anti-wearing properties.
- Good rust, corrosion and foaming prevention.
- Suitable with all impermeability components.

CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Ideal Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8780
Viscosity, 40°C	cSt	ASTM D 445	47,16
Viscosity, 100°C	cSt	ASTM D 445	7,10
Viscosity Index		ASTM D 2270	108
Pour Point	°C	ASTM D 97	-33
Flash Point	°C	ASTM D 92	230

SuperMax Oil Germany Steering Fluid

STORAGE

Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use. Packages should not be exposed to direct sunlight and avoid rapid climatic changes. Ambient temperature should not exceed 60 °C.

SHELF LIFE

Under the appropriate storing conditions suitable to the declared circumstances, maximum shelf life of the products are two years.

HEALTH AND SAFETY

Based on the available information, SuperMax Oil Germany Steering Fluid is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Material Safety Data Sheet" (MSDS). MSDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations.